

SPECIFICATIONS

FinePix Z35	
Number of effective pixels*	10.0 million pixels
CCD sensor	1/ 2.3-inch CCD
Storage media	Internal memory (Approx. 18MB) SD memory card / SDHC memory card*2
File format	Still image: JPEG (Exif Ver. 2.2*) Movie: AVI (Motion JPEG) with sound / Audio: WAVE format, Monoaural sound (Design rule for Camera File system compliant / DPOF-compatible)
Number of recorded pixels	Still image: 3,648 x 2,736 (10M) / 3,648 x 2,432 (3.2 format) / 2,592 x 1,944 / 2,048 x 1,536 / 1,600 x 1,200 / 640 x 480
Lens	Fujinon 3 x optical zoom lens, F3.7(Wide)-F4.2(Telephoto)
Lens focal length	f=6.5 - 18.1mm, equivalent to 35-105mm on a 35mm camera
Digital zoom	Approx. 5.7x
Aperture	Wide: F 3.7 - F 8.0, Telephoto: F4.2 - F 9.0
Focus distance (from lens surface)	Normal: Wide: Approx. 60cm/2.0 ft. to infinity, Telephoto: Approx. 60cm /2.0 ft. to infinity Macro: Wide: Approx. 8cm - 80cm / 3.2 in.- 2.6ft., Telephoto: Approx. 60cm - 3.0m / 2.0 ft.- 9.8 ft.
Sensitivity	Auto / Equivalent to ISO 100 / 200 / 400 / 800 / 1600 (Standard Output Sensitivity)
Exposure control	TTL 256-zones metering
Exposure mode	Programmed AE
Shooting modes	SR AUTO, Auto, Natural Light, Manual, Anti-blur SP: Portrait, Landscape, Sport, Night, Night(Tripod), Sunset, Snow, Beach, Party, Flower, Text
Image Stabilizer	Anti-blur
Shutter speed	(All modes) 3 sec. to 1/1000 sec.
Continuous shooting	Top-3 (max 1.0 frames/sec)
Focus	Auto focus
White balance	Automatic scene recognition Preset: Fine, Shade, Fluorescent light (Daylight), Fluorescent light (Warm White), Fluorescent light (Cool White), Incandescent light
Self-timer	Approx. 10 sec. /2 sec. delay
Flash	Auto flash Effective range: (ISO AUTO): Wide: Approx. 70cm - 3.1m / 2.3 ft. - 10.1 ft. Telephoto: Approx. 70cm - 2.7m / 2.3ft. - 8.8 ft. Macro: Approx. 30cm - 80cm / 1.0 ft. - 2.6 ft. Flash modes : Red-eye removal OFF: Auto, Forced Flash, Suppressed Flash, Slow Synchro. Red-eye removal ON: Red-eye Reduction Auto, Red-eye Reduction & Forced Flash, Suppressed Flash, Red-eye Reduction & Slow Synchro.
LCD monitor	2.5inch, Approx. 230,000 dots, TFT color LCD monitor, Approx. 96% coverage
Movie recording	640 x 480 pixels / 320 x 240 pixels (30 frames/sec.) with monoaural sound
Photography functions	SR Auto(Scene Recognition Auto),Face Detection, Auto red-eye removal, Framing guideline, Frame No. memory, Silent mode
Playback functions	Face Detection, Auto red-eye removal, Slide show, Trimming, Trimming for blog, Playback type, Multi-frame playback (with Micro Thumbnail), Sorting by date, Image rotate, Voice Memo
Video output	NTSC / PAL selectable
Digital interface	USB 2.0 High-speed
Power supply	NP-45A Li-Ion battery (included), AC power adapter(included)
Dimensions	89.0 (W) x 57.9 (H) x 23.9 (D) mm / 3.5 (W) x 2.3 (H) x 1.0 (D) in. (excluding accessories and attachments)
Weight	Approx. 115 g / 4.1 oz. (excluding accessories, battery and memory card)

Number of images / recording time

Mode	Still image						Movie		
	3,648x2,736		3,648x2,432(3:2)		2,592 x 1,944		640 x 480		
Number of recorded pixels									
Quality	JPEG FINE	JPEG NORMAL	JPEG	JPEG	JPEG	JPEG	VGA (30fps)	QVGA (30fps)	
Internal memory (approx. 18MB)	3	7	8	15	21	28	125	35 sec.	41 sec.
SD memory card	95	180	210	350	480	640	2200	6 min.	14 min.
1GB	190	380	420	700	960	1280	4420	12 min.	28 min.
2GB	390	760	860	1400	1930	2580	8850	25 min.	57 min.
SDHC memory card	4GB	790	1520	1720	2810	3870	5160	50min.**	116 min.**
8GB	1590	3060	3460	5660	7780	10380	35600	102min.**	233 min.**

* Actual number of frames and recording time varies depending on the types of memory card or shooting conditions.
** A movie recording will stop automatically when the movie file size becomes approx. 2GB.

* 1 : Number of effective pixels: The number of pixels on the image sensor which receive input light through the optical lens, and which are effectively reflected in the final output data of the still image.
* 2 : Please see the Fujifilm website to check memory card compatibility.
* 3 : Exif 2.2 is a digital camera file format that contains a variety of shooting information for optimal printing.
* 4 : *CIPA DC-002-2003 Standard Procedure for Measuring Digital Still Camera Battery Consumption* (extract) Pictures shall be taken at a temperature of 23°C, with the LCD monitor turned on, the zoom moved from full wide-angle to full telephoto (or vice-versal) and back again to its original position every 30 seconds, the flash used at full power every second shot and the camera turned off and then on again once every 10 shots.

Windows Vista and the Windows logo are trademarks of the Microsoft group of companies.
Macintosh and Mac OS are trademarks of Apple Computer, Inc., registered in the U.S. and other countries.
SD logo is a trademark. All other trademarks are the property of their respective holders.

FUJIFILM
FUJIFILM Corporation

COLOR VARIATIONS



OPTIONAL ACCESSORIES

Li-ion battery
NP-45



Battery charger BC-45
A/V cable AV-C1

Accessory availability may vary by country.
Please check with your local Fujifilm representative
to confirm product availability.

ACCESSORIES INCLUDED

- Li-ion battery NP-45A
- AC power adapter
- Hand strap
- USB cable for the FinePix Z35
- CD-ROM : FinePixViewer
- Owner's manual

Guide to the number of available frames for battery operation

Battery	LCD monitor status	Number of frames
NP-45A	LCD monitor ON	Approx. 165 frames

According to the Camera & Imaging Products Association (CIPA) standards**; The battery (NP-45B) is supplied with the camera.



Specifications are subject to change without notice.

For more information, please visit our Website:

http://www.fujifilm.com/products/digital_cameras/index.html

FUJIFILM

FINEPIX Z35 NEW



*Style meets
Technology!*


10 Megapixels

3x Optical Zoom

SR AUTO (Scene Recognition Auto)

FinePix. More than you imagined.

Scene Recognition Auto



 Portrait




 Night




 Landscape



 Macro



 Backlit Portrait



 Night Portrait

With SR Auto, you will never miss another moment!
 Just frame the fun and SR Auto automatically recognizes 6 different scene types, sets the perfect mode and instantly fine tunes not only exposure and focus, but also sensitivity and white balance for stunning photos every time. Skin tones in portraits are more natural! Night shots are clearer. Capture detail in landscapes! Shoot exceptional close-up macro photos. Taking quality backlit portraits and photos in other challenging lighting scenes is so easy with SR Auto.



Style outside,
high performance inside—
 all in a compact body!

Fun Features and Smart Functions for More Great Photos!

10 Megapixel and 3x Optical Zoom

10 megapixels of resolution produces impressive, crisp, clear pictures, perfect for cropping or enlarging as you like. With the 3x zoom incorporated in the slim body, get closer to the action without having to move.

High Sensitivity ISO 1600 & Anti-Blur Mode (Picture Stabilization)

Say goodbye to dark photos and blurry images. High sensitivity not only captures dark scenes with the right brightness, but also prevents blur from camera shake and moving subjects by letting you use a faster shutter speed.



Conventional digital camera



FinePix Z35

Make Your Own Movies and Share It on YouTube!

At a touch of a button, shoot movies. Just press, shoot and enjoy the movie! You can also share the movie with friends on YouTube using Fujifilm's NEW FinePix Viewer software (included).

Face Detection with Auto Red-eye Removal

Face Detection automatically detects faces, setting focus and exposure for clear, sharp faces with natural skin tones. And with Automatic Red-eye Removal, the Z35 automatically checks for and corrects red eyes in detected faces both when shooting and playback.

2.5" LCD & Micro Thumbnail

Show off the beautiful results on the spot on the large 2.5" LCD. The convenient 10 x 10 Micro Thumbnail View lets you navigate and find photos in an instant.

