

## A stylish range of slim-line compact cameras



Silver



Black



Champagne Gold



Blue



Red



Pink



**14** Megapixels

Fujinon **3x** Zoom Lens

**2.7"** LCD (230,000 dots)

Body Thickness  
**18.5** mm<sup>\*1</sup>

**ISO 3200**<sup>\*2</sup>

**SR AUTO**  
Automatic Scene Recognition

**Auto Red-eye Removal**

**Digital Image Stabilization**

**Smile & Shoot**

**Blink Detection**

**i-Flash**

**Natural Light & with Flash**

**Tracking AF**

**PANORAMA**  
Motion Panorama

**Photobook Assist**

**Image Search**

**Micro Thumbnail**

**Web Upload**

<sup>\*1</sup>: Minimum depth

<sup>\*2</sup>: ISO3200 is effective in S mode

## 14 Megapixels


An impressive 14 megapixel resolution never misses the finest details of your subject, capturing sharp and clear images in vivid colors, even when printed in large size.

## Fujinon 3x Zoom Lens

World renowned Fujinon lens technology, as used in space satellite, TV/film, security and compact cameras, provides a great wide angle and 5x optical zoom.



1x




3x optical zoom

## SR AUTO Automatic Scene Recognition

Framed scenes are automatically detected and selected into appropriate camera settings: Portrait, Landscape, Night, Macro, Night Portrait, and Backlit Portrait.

**Portrait**




**Landscape**



**Night**



**Macro**



**Night Portrait**



**Backlit Portrait**



## 《手》 Digital Image Stabilization

Digital Image Stabilizer reduces blurring caused by camera shake using high sensitivity and fast shutter speed. Captures crisp and clear images of moving subjects.



Conventional digital camera



FinePix JV200

## HD MOVIE HDTV Compatible Movies

FinePix JV200 can produce both photos and movies in high-definition 16:9 format, letting you discover the impact of full-screen HDTV images.

**Option**  
**HD Player HDP-L1**



## N Natural Light & with Flash

Not sure whether you need the flash? Natural Light & with Flash takes two photos in quick succession, one with flash and one without, eliminating the guesswork of flash photography.



Natural Light (flash off)



With Flash

## Image Search

With the convenient Image Search function, you can search photos by Date, Face, Scene, Type of Data or Favorite Rank, by Upload Mark.



by Favorite	by Scene
by Face	by Type of Data
by Date	by Upload Mark

## Web Upload



With a PC connected, the marked images can be easily uploaded to the designated site, without time-consuming PC-based image processing or selection.



## Photobook Assist

With the Photobook Assist function, you can easily create a Photobook by sorting and tagging images.

- [1] Select images
- [2] Check the images on the LCD
- [3] Create a Photobook at the shop easily



The above is a rendered image

## Specifications

Number of effective pixels <sup>*1</sup>	14.0 million pixels
Image sensor	1/2.3-inch CCD with primary color filter
Storage media	SD memory card / SDHC memory card <sup>*2</sup>
File format	Still image: JPEG (Exif Ver 2.3 <sup>*3</sup> ) / (Design rule for camera file system compliant / DPOF-compatible)
Number of recorded pixels	Still image: L: <4.3> 4288 × 3216 <3.2> 4288 × 2864 <16.9> 4288 × 2416 / M: <4.3> 3072 × 2304 <16.9> 3072 × 1728 / S: <4.3> 2048 × 1536 <16.9> 1920 × 1080
Lens	Fujinon 3x optical zoom lens
Lens focal length	≒6.5 - 19.5 mm, equivalent to 36 - 108 mm on a 35 mm camera
Digital zoom	Approx. 6.7x (up to approx. 20.1x, with 3x optical zoom)
Aperture	F3.1 / F8.0 (Wide) F5.6 / F14.4 (Telephoto) with ND filter
Focus distance (from lens surface)	Normal: Wide: approx. 45 cm to infinity / 1.5 ft. to infinity, Telephoto: approx. 80 cm to infinity / 2.6 ft. to infinity Macro: Wide: approx. 5 cm - 80 cm / 2.0 in.-2.6 ft., Telephoto: approx. 50 cm - 1.0 m / 1.7ft. - 3.3ft.
Sensitivity	Auto / Equivalent to ISO 100 / 200 / 400 / 800 / 1600 / 3200 (Standard output sensitivity) ISO 3200 is effective in S mode.
Shooting modes	SR AUTO, AUTO, P, Movie, Natural Light & with Flash, Natural Light, Portrait, Baby, Smile, Landscape, Panorama, Sport, Night, Night (Tripod), Fireworks, Sunset, Snow, Beach, Party, Flower, Text
Shutter speed	(Auto mode) 1 / 4 sec. to 1 / 1400 sec. (All other modes) 8 sec. to 1 / 1400 sec.
LCD monitor	2.7-inch, approx. 230,000 dots, TFT color LCD monitor, approx. 96% coverage
Movie recording	1280 x 720 pixels / 640 x 480 pixels / 320 x 240 pixels (30 frames / sec.) with monaural sound, Zoom function can be used, Sounds will not be recorded during optical zoom operation.
Power supply	NP-45A Li-ion battery (included)
Dimensions	94.0 (W) × 56.2 (H) × 20.9 (D) mm / 3.7 (W) × 2.2 (H) × 0.8 (D) in. (Minimum depth: 18.5 mm / 0.7 in.)
Weight	Approx. 108 g / 3.8 oz. (excluding accessories, battery and memory card)

<sup>\*1</sup>: Number of effective pixels: The number of pixels on the image sensor which receive input light through the optical lens, and which are effectively reflected in the final output data of the still image.

<sup>\*2</sup>: Please see the Fujifilm website to check memory card compatibility.

<sup>\*3</sup>: Exif 2.3 is a digital camera file format that contains a variety of shooting information for optical printing.

For more information, please visit our website:

[http://www.fujifilm.com/products/digital\\_cameras/index.html](http://www.fujifilm.com/products/digital_cameras/index.html)

Specifications are subject to change without notice.

All sample photos are simulated images.